

complett

MACCHINE PER CUCIRE INDUSTRIALI
INDUSTRIAL SEWING MACHINES



■ SETTORE MAGLIERIA

■ KNITWEAR FIELD

88 VARIO



Rimagliatrice
con sistema **vario**



Linking Machine
with **vario** system

■ Punto tipo "101"

■ Stitch type "101"



■ Ago a cruna dall'interno della corona.

■ Eye needle approaching from
the inside of the dial.

www.complett-ks.it



**Sistema
VD**

Motore brushless con variatore velocità continua fino ad un massimo di 900 punti/minuto a secondo delle finzze e filati utilizzati.

Consumo di energia molto basso (**115 watt**).

Predisposto sia per corrente monofase che trifase.

**CARATTERISTICHE
TECNICHE**

- Montaggio della maglia dal rovescio
- Catenella ad 1 filo
- **Sistema di posizionamento dell'ago**
- Arresto ago di sicurezza
- Nuova pedana girevole con rotazione facilitata
- Pedale a doppia velocità
- Rotazione oraria o anti-oraria (a richiesta)
- Testa girevole
- Puntine in acciaio inossidabile
- Diametro della corona molto grande mm 460
- Finezze da 3 a 24 intercambiabili
- **Angolo di inclinazione delle puntine a 30°**

PESI

Netto	Kg 87
Lordo	Kg 122

Dimensioni imballo

cm 139 x 76 x 106



**VD
System**

Brushless motor with variable speed drive, continuous speed up to maximum 900 stitches/minute according to the gauge sizes and threads used.

Very low power consumption (**115 watt**).

Suitable for single phase as well as three-phase motor.

**TECHNICAL
FEATURES**

- The fabric is loaded on the reverse side
- Single thread chainstitch
- **Needle positioning system**
- Safety needle stop device
- New easy turning footboard.
- Double-speed pedal.
- Clockwise or anticlockwise dial motion (on request)
- Rotable head.
- Stainless steel points.
- Extra large dial mm. 460 diameter.
- Interchangeable gauges: sizes from 3 to 24
- **Angle of inclination of the points at 30°**

WEIGHTS

Net	Kg 87
Gross	Kg 122

Packing dimensions

cm 139 x 76 x 106



SISTEMA "VARIO" BREVETTO COMPLETT

Gruppo tensione elettronica programmabile con fotocellula che permette l'applicazione selettiva di varianti di tensionamento del filato durante l'operazione di rimaglio.

- **FOTOCELLULA:** (disattivabile) legge la presenza del tessuto e permette la selezione di diverse tensioni in "cucitura" e in "catenella a vuoto".
- **POSSIBILITÀ 3a TENSIONE:** (a comando ginocchiera o pulsante) per cucire il tessuto con tensioni diverse durante l'operazione di rimaglio.
- **MEMORIA:** 5 programmi, ognuno dei quali permette di memorizzare 3 tensioni e 4 velocità diverse.
- **FUNZIONE AGO-STOP:** si può selezionare l'arresto "Ago fuori" e "Ago dentro".

"VARIO" SYSTEM COMPLETT PATENT

Programmable electronic tension unit with photocell that allows the selective application of yarn tension variations during the linking operation.

- **PHOTOCELL:** (it can be deactivated) it "detects" the fabric and allows the selection of various tensions both while "stitching" and when "idling".
- **POSSIBILITY OF A THIRD TENSION:** (knee or button driven) to sew fabric with different tensions during the stitching operation.
- **MEMORY:** 5 programmes, each one allows to memorise 3 tensions and 4 different speeds.
- **NEEDLE-STOP FUNCTION:** You can select the stop option "Needle out" and "Needle In".



Gruppo tensione elettronica programmabile

Programmable electronic tension unit



INDUSTRIA 4.0

Possibilità di interconnettersi tramite i maggiori protocolli standard.

Recupero immediato di informazioni tecniche e gestionali in tempo reale.

INDUSTRY 4.0

Ready to be connected with standard protocols.

Immediate recovery of technical information and management in real time.